NITROREDUCTASE BIOSENSORS FOR DETECTING NITRO-COMPOUNDS

Field of the Invention

5   This invention relates to biosensors, methods of sensing nitro-compounds and modified enzymes per se.   In particular, but not exclusively the invention relates to biosensors, methods of detecting nitro-compounds and modified enzymes useful in detecting explosives.

10

Background to the Invention

Biosensors generally comprise a class of devices that recognise a desired compound (analyte) in a sample and
15   generate a signal which can be resolved to determine the concentration of the compound within the sample.   Most biosensors are based on their ability to distinguish a specific analyte, or limited range of analytes, without the need for separation or isolation.   For example there
20   are known biosensors which can detect the presence of particular compounds within a blood or water sample directly, thereby eliminating the need for a lengthy or complex purification steps to recover the analyte of interest.

25

Many biosensors rely on the coupling of a recognition system with an electrochemical or optical transducer to produce an electrical or optical signal or impulse when the recognition system recognises an analyte, which is
30   then used in analyte concentration determination. Electrochemical transducers used in biosensors include potentiometric and amperometric transducer mechanisms.

Optical based transducer mechanisms include fluorescence, phosphorescence and a simple colour change.

In potentiometric-based biosensors the accumulation of charge density at the surface of an electrode is measured and is representative of the concentration of analytes to which a biosensor is exposed. In amperometric sensors, electrons that are exchanged between a biological system and an electrode generate a current which may be monitored to determine the concentration of analytes within their sample. Amperometric sensors are commonly employed in blood glucose and ethanol sensors, as well as other devices which monitor compounds of biological significance. In many biosensors a biological recognition molecule performs part of the sensor. The biological recognition molecule may be a nucleic acid sequence, an RNA, or more commonly a protein such as an enzyme or antibody. The biological recognition molecule binds specific analytes, or a limited range of analytes, and is therefore ideally suited for selective detection of specific analytes.

Charge transfer is either accomplished by low molecular weight redox co-factors, such as the NAD^+/NADH or by the direct interaction of the redox centres of proteins. Both types of biochemical charge transfer reactions have been previously coupled to redox electrodes. Electrochemistry provides a useful tool for studying the redox chemistry associated with enzymes. A method that can be used to evaluate electron transfer between enzymes and an electrode is the indirect method of using a small redox molecule serving as an electron transfer co-factor. The scheme of the electron transfer coupling is illustrated in

figure 1, where the enzymatic (E_O/E_R) reaction for the oxidation (or reduction) of the substrate is linked to the electrochemical reduction (or oxidation) of the co-factor (C_O/C_R) by the electrode as a final electron acceptor (or donor). The enzyme catalysed electrochemical oxidation (or reduction) of the substrate is called bioelectrocatalysis.

The enzyme electrode is a combination of any electrochemical probe (amperometric, potentiometric or conductometric) with a thin layer (10-200μm) of immobilised enzyme. In these devices, the function of the enzyme is to provide selectivity by virtue of its biological affinity for a particular substrate molecule.

However there are problems in attaching many biological recognition molecules to biosensors. Many biological recognition molecules such as enzymes, and antibodies have "active sites" which must be presented to the analyte in order for the analyte to bind the biological recognition molecule. For many biological recognition molecules, attachment to a biosensor may obscure or hinder the active sites, and therefore render the biological recognition molecule less effective, or, in some cases, inactive.

Of growing interest is the detection of nitro compounds present in many explosives and explosive precursors such as fertiliser.

Interest is growing not only for the detection of buried munitions from previous wars, but also through interest in detecting explosives on a person's body, a person's possessions, vehicles and structures.

For buried or unexploded munitions, there is a great hazard that members of the public working in areas where the explosives are buried, may plough up or step on unexploded ordinance, without being aware that explosives are present at all.

Currently there are sensing systems available to detect explosives, which include for instance the system described in US 5972638, in which a modified organism of the *Pseudomonas* species or *Bacillus* species are sprayed onto ground believed to contain buried explosives. The ground is gently irradiated before spraying on the organism, in order to increase explosive vapour concentration in the soil. This system is relatively expensive, and requires equipment in the form of crop spraying aircraft, spraying devices and irradiation devices. Furthermore, the ground requires substantial quantities of modified organism to be sprayed onto the surface, in order that a detectable signal is achievable.

In WO 97/03201 and GB 2303136, nitroreductase enzymes per se are purified and used to detect nitrates in samples of soil or otherwise, by way of a calorimetric method. The nitroreductase used in these patents is a pentaerythritol tetra nitratereductase, which is specific only for PETN. Furthermore, the concentration level of nitrates which can be detected is relatively high and in order for detection to take place, a soil sample must be removed from the ground, and taken away for a relatively time consuming and complicated assay procedure.

It would therefore be advantageous to provide a biosensor, able to detect explosives in situ, whether in soil or other ground material, or in a sample of material.

5   It would furthermore be advantageous to provide a highly sensitive detection system for nitro-compounds commonly present in explosives and fertilizers, which is able to detect in at least the nanomolar, but more preferably the picomolar concentration range.

10

It is an aim of preferred embodiments of the present invention to overcome or mitigate at least one problem of the prior art, whether expressly disclosed herein or not.

15   **Summary of the Invention**

According to a first aspect of the invention there is provided a sensing device comprising an electrode comprising a noble metal layer, on which layer is located

20   a biological material having nitroreductase activity.

Preferably the noble metal layer comprises a noble metal selected from the group consisting of gold, silver, platinum, palladium, iridium, rhenium, ruthenium and

25   osmium, or alloys or mixtures thereof. More preferably the noble metal is gold, platinum, or alloys or mixtures thereof, but is most preferably gold.

The noble metal layer preferably comprises at least a top

30   and bottom surface, and suitably the biological material is located on one of the top and bottom surfaces.

Preferably the biological material is immobilised on the noble metal layer. The biological material is preferably present as a layer on the noble metal layer. The biological material layer is preferably a self-assembled layer.

Suitably the biological material comprises a plurality of sulphur-containing functional groups, preferably sulphydryl (-SH) groups.

Suitably biological material is a protein. Suitably the protein is selected from an enzyme, antibody, receptor, antibody fragment, or binding protein, but is most preferably an enzyme.

Preferably the enzyme is a nitroreductase.

Suitably the nitroreductase is encoded by the *nfnB* gene (SEQ ID1) in *Escherichia coli* or the *pnrA* gene (SEQ ID2) in *Pseudomonas putida*. (the native enzymes are referred to hereinafter as "*nfnB*" and "*pnrA*" respectively). Suitably the nitroreductase is encoded by a nucleic acid sequence substantially as set out in SEQ ID1 or SEQ ID2.

The biological material may be covered by a fluid permeable cover layer, preferably in the form of membrane. The cover layer may comprise a polycarbonate or polyacrylate material and is preferably between 1 and 100 μm in thickness, more preferably between 5 and 50 μm, still more preferably between 8 μm and 30 μm and most preferably between 10 and 20μm.

The noble metal layer is preferably mounted on an insulating substrate. The insulating substrate may be selected from glass, quartz, silicon, insulating polymers, plastics, and mixtures thereof.

The noble metal layer may be connected on a surface not comprising the biological material, to one or more layers of conductive, semi-conductive or insulating material. Conductive and semi-conductive materials include metals, alloys, carbon paste, graphite and conducting polymers such as polpyrrole, polyaniline, polythiophene, polypyrimidine and the like for example. The one or more further layers may be located between the noble metal layer and the insulating substrate, when present.

In particularly preferred examples the sensing device comprises a gold layer on which is self-assembled a layer of nitroreductase enzyme which has been modified to include a plurality of cysteine residues at a location on the enzyme which does not substantially interfere with the activity of the enzyme.

The nitroreductase may comprise substantially the expression product of the nucleic acid sequence shown in SEQ ID3, which comprises the nucleotide sequence between the T7 promoter and the T7 terminator of the pET-28a(+) plasmid containing the *Escherichia coli* K12 *nfnB* gene, in which 6 cysteine residues (a "Cys_6" tag) have been inserted at the N-terminal end.

Another preferred nitroreductase comprises substantially the expression product of the nucleic acid sequence shown in SEQ ID5, which is the nucleic acid sequence between the

T7 promoter and the T7 terminator on the plasmid pET-28a(+) containing the *Pseudomonas putida* JLR11 *pnrA* gene in which a Cys$_6$ tag has been inserted at the N-terminal end.

The amino acid translation products of SEQ ID3 and SEQ ID5 are given in SEQ ID4 and SEQ ID6 respectively. Suitably the modified nitroreductase comprises a polypeptide sequence substantially as set out in SEQ ID4 or SEQ ID6.

The nitroreductase may be operably associated with an electron mediator, such as a ferrocene, a phthalocyanate or the like, foe example.

According to a second aspect of the invention there is provided a sensing system comprising a sensing device of the first aspect of the invention, mounted in an electrochemical cell.

The electrochemical cell preferably comprises, in addition to the sensing device, a reference electrode. More preferably the electrochemical cell comprises both a reference electrode and a counter-electrode.

The reference electrode may comprise a Calomel electrode (Standard Calomel Electrode (SCE)), Hg/Hg$_2$Cl$_2$ electrode and/or Ag/AgCl electrode, or any combination thereof. Ag/AgCl electrodes are preferred as they may be manufactured in various forms, for example discs, wires, rods, layers etc.

The electrochemical cell may comprise a housing constructed from glass, polystyrene or the like, for example.

5   The sensing system may be operably connected to a measuring instrument, such as a voltammeter, amperometer, cyclic voltammeter, or the like, for example.

According to a third aspect of the invention there is
10   provided a method of detecting nitro group-containing compounds, the method comprising the steps of:

      (a) providing a sensing device of the first aspect of the invention and a reference electrode;

      (b) applying a potential between the electrodes;

15   (c) measuring the current;

      (d) contacting the sensing device with sample of substrate material to be tested; and

      (e) measuring the current change.

20   The method may comprise a further step (f) of subtracting the current change measured with a blank electrode from the value obtained in step (e). The blank electrode may be the sensing device of the first aspect of the invention which either does not contain the biological material, or
25   contains inactivated biological material.

Depending on the physical type of the sensing device of the first aspect of the present invention, there may be a step between steps (a) and (b) of placing the sensing
30   device in a measuring solution. In this case step (d) may comprise adding a sample of the material to be tested, to the measuring solution.

According to a fourth aspect of the present invention there is provided a protein comprising a nitroreductase enzyme which has been modified to comprise a plurality of cysteine residues incorporated into its structure.

5

According to a fifth aspect of the present invention there is provided an isolated nucleic acid sequence comprising a nitroreductase gene modified by the addition of a plurality of codons for cysteine residues.

10

Suitably the nitroreductase gene is selected from the *Escherichia coli* K12 *nfnB* gene and the *Pseudomonas putida* JLR11 *prnA* gene. The nucleic acid sequences for the *nfnB* and *pnrA* genes are given as SEQ ID1 and SEQ ID2

15 respectively and preferably the nitroreductase gene is encoded by a nucleic acid sequence substantially as set out in SEQ ID1 and SEQ ID2. Suitably the cysteine codons are incorporated at or in the region of the 3' end of the nucleic acid.

20

According to a sixth aspect of the present invention there is provided a nucleic acid construct comprising:

(a) a promotor for the expression of a nitroreductase gene;

25   (b) a plurality of codons for Cys residues; and

(c) a nucleotide sequence of a nitroreductase gene;

Suitably the nitroreductase promoter is the T7 promoter from pET-28a(+).

30

Suitably the construct comprises the pET-28a(+) plasmid.

Preferably the construct is a vector substantially
comprising the nucleic acid sequences shown in SEQ ID3 or
SEQ ID5, the reverse complement of the said sequences, the
complement of the said sequences, the reverse of the said
sequences, or sequences having at least 60% sequence
identity with the nucleic acid sequences of any one of the
aforementioned sequences.

By use of the term "at least 60% identity" it is therefore
understood that the invention encompasses more than use of
the specific exemplary nucleotide sequences.
Modifications to the sequence such as deletions,
insertions, or substitutions in the sequence which produce
either:
a) "silent" changes which do not substantially affect the
functional properties of the protein molecule. For
example, alterations in the nucleotide sequence which
reflect the degeneracy of the genetic code or which result
in the production of a chemically equivalent amino acid at
a give site are contemplated, or:
b) promote improvements in activity or modifications in
substrate specificity are also contemplated.

A modification of the nucleotide sequence with an identity
greater than 80%, preferably more than 85%, more
preferably more than 90% and most preferably more than 95%
of SEQ ID 1 or 2 is envisaged.

It has been surprisingly found that the incorporation of
cysteine resides in nitroreductases enables efficient
incorporation of the nitroreductase onto a noble metal
electrode which effects sensitivity of nitrocompound
detection down to the picomolar concentration range. Most

known nitrocompound detection system enable detection down to the nanomolar range only, and it is believed the conjugation of the nitroreductase and noble metal electrode via cysteine linkages enables optimal orientation of the enzyme on the electrode, leading to enhanced sensitivity. The immobilisation of nitroreductase onto noble metal electrodes via introduced cysteine residues, on the enzyme, is also relatively cheap and uncomplicated. The resultant sensing devices are able to be reused many times and can be used *in situ*, or in site to detect buried explosives in ground, or in samples taken from suspected explosive-containing materials.

EXAMPLES

For a better understanding of the present invention and to show how embodiments are the same may be put into effect the invention will now be described by way of example only with reference the accompanying drawings in which:

Figure 1 illustrates a general model of a modified electrode, showing the mediation of electron transfer.

Figure 2 illustrates the pET-28a(+) plasmid;

Figure 3 illustrates a partial nucleotide sequence of the pET-28(a)(+) plasmid from the T7 promoter to the T7 terminator region;

Figure 4 illustrates a graph showing the influence of a Cys_6 tagged *nfnB* nitroreductase on a buffer solution containing 4-nitrobenzoate and its UV-viz absorbance spectrum;

Figure 5 illustrates a bar chart showing the activity of a Cys$_6$ tagged nfnB nitroreductase on various substrates;

5   Figures 6A and 6B illustrate the activity of desalted and non-desalted forms of a Cys$_6$ modified nfnB nitroreductase in catalysing breakdown of 2,4- dinitroethylbenzene;

Figure 7 illustrates activity of a Cys$_6$ modified nfnB
10 nitroreductase utilising ferrocene dicarboxylic acid as a cofactor;

Figure 8 illustrates a plot of the activity against increasing concentrations of substrates of a Cys$_6$ modified
15 nfnB nitroreductase;

Figure 9 illustrates a cyclic voltammograms of a Cys$_6$ modified nfnB nitroreductase immobilised on a golf slide and a control gold slide without attached enzyme;

20

Figure 10 illustrates cyclic voltammograms of a Cys$_6$ modified nfnB nitroreductase utilising ferrocene dicarboxlic acid as a cofactor;

25 Figure 11 shows the amperometric response of a biosensor utilising nfnB Cys$_6$ modified enzyme expressed from a construct at a fixed potential of +100mV; and

Figures 12A and 12B illustrate amperometric measurements
30 of a Cys$_6$ modified nfnB nitroreductase containing biosensor with 10, 30, 40 and 50 pmoles 2,4 dinitroethylbenzene.

Example 1 - Preparation of a plasmid comprising a modified *nfnB* gene from *Escherichia coli* K12. Plasmids containing *nfnB* genes from *Escherichia coli* K12 modified by addition of codons for a Cys$_6$ tag were prepared in the following
5   manner.

1.1 <u>The procedure for obtaining the original DNA templates</u>
The DNA template was prepared by introducing cells *Escherichia coli* K12 into a solution of TE buffer pH 7.5
10   (Tris-Cl, ethylenediaminetetraacetic acid (EDTA)) (100 μl, 1%) in an eppendorf tube. The resulting suspension was mixed thoroughly and boiled for 5 min to break down the cell structure, releasing the DNA into the solution, and was then cooled on ice and centrifuged for 2 min. The
15   centrifuge was set to operate at 14000 rpm unless otherwise stated.
1.2 <u>Polymerase chain reaction (PCR) protocol for the nitroreductase DNA</u>

20   The PCR protocol uses a standard commercial kit (ProofStart™, Qiagen, UK) according to the manufacturer's instructions.

Template DNA (*Escherichia coli* K12) (1 μl) was amplified
25   by PCR using the standard procedure with primers conforming to SEQ ID7 (5 μl), and to SEQ ID8 (5 μl)

The PCR system was programmed to run in the following manner. The system was held at 95°C for 5 min in order to
30   activate the DNA polymerase. The subsequent temperature cycle consisted of 94°C for 30s to separate the DNA strands, 62°C for 1 min for annealing with the primers, 74°C for 2 min for replicating the double stranded DNA.

This sequence was repeated for 35 cycles, after which the
temperature was held at 74°C enabling any uncompleted
double strands to complete. An aliquot of the solution
was then run on a 1% agarose gel, in 1x Tris-Borate-EDTA
5   (TBE) buffer pH 8.2 containing ethidium bromide. The
ethidium bromide acts as a stain enabling the molecular
weight and purity of the DNA to be determined by viewing
against a sample containing DNA fragments of known
molecular size run in the same gel. The remaining DNA
10   from the PCR was purified to remove the primers,
nucleotides, polymerase, and salts, in preparation for
other enzymatic reactions as follows.

15   1.4 Cloning of the nitroreductase gene
Ligation is the incorporation of the DNA into a plasmid.
A good efficiency of ligation of foreign DNA into a
plasmid can be achieved if both the plasmid and the insert
DNA are cut with two different restriction enzymes, which
20   leave single-stranded, cohesive ends. The DNA is thus
ligated in only one predetermined direction.
The PCR product (5 µl) was mixed with the appropriate
restriction enzymes (2 µl of each), purified water (2 µl),
and 10x appropriate restriction buffer solution (1 µl). A
25   separate solution was made up of the expression plasmid
pET-28a(+) (5 µl) (Novagen, UK; Figures 2 and 3). The
region between the T7 promoter and T7 terminator is shown
in Figure 3. This was mixed with the same two restriction
enzymes   (1 µl of each) plus a third, EcoRI (1 µl),
30   purified water (1 µl), and 10x buffer solution (1 µl): the
EcoRI digestion ensures that the pET28a(+) plasmid does
not religate without an insert. Each solution was

incubated at 37° for 1 hour to allow the restriction digestion to occur, after which each was cleaned up according to section 1.3. Both were dried under vacuum and redissolved in purified water (4 µl).

The two solutions were then mixed and DNA ligase (1 µl), and ligase 10x buffer solution (1 µl), were added. This solution was then maintained overnight at 16°C for the ligation process. To check that the ligation of the PCR product between the T7 promoter and T7 terminator of pET-28(a)(+) was successful an aliquot of the ligation mix was digested with the appropriate restriction enzymes (1 µl each) as described above and subjected to agarose gel electrophoresis.

The remaining ligation mixture was mixed with cells of competent *E. coli* DH5α (200 µl), an efficient strain of *E. coli* for plasmid maintenance. In order to transform the recombinant plasmid into the competent cells, the mixture was left on ice for 30 min, was then heated to 42°C for exactly 50 sec and then returned to ice for 2 min. The resulting culture was added to Luria-Bertani (LB) medium (500 µl), incubated at 37°C for 45 min, and then applied to the Petri dishes.

1.5 Growing the colonies

The solid medium consisted of LB agar containing the antibiotic kanamycin (50 µg/ml). This medium will only allow bacteria carrying the recombinant plasmid to grow, as a kanamycin resistance gene is an integral part of pET28a(+). The transformed *E. coli* culture was spread

onto the plates in a range of different concentrations. Single colonies, which grew were then transferred to liquid LB medium (5 ml) containing kanamycin (50 µg/ml) and grown overnight at 37°C.

The recombinant plasmid was isolated from the overnight cultures after separating the cells as a pellet following centrifugation. A standard QIAprep Spin Miniprep Kit (Qiagen, UK) was used to purify the plasmid according to the manufacturer's instructions.

1.7 PCR protocol for the incorporation of the Cys_6 sequences.

Using purified pCDG1 as template DNA, the protocol for PCR was repeated using designed primers conforming to SEQ ID9 and to SEQ ID8: these contain six adjacent codons for Cys at the 3' end of the nitroreductase such that when the gene is expressed an amino acid sequence of Cys_6 is added to the N-terminus of the protein, between the His_6-tag determined by pET28a(+) and the start codon of the nitroreductase. The same protocols as described above for cloning the modified gene, transforming it into *E. coli* DH5α, and purifying it were used. The resultant plasmid was named pMKS2.

Example 2 - Expression of the Cys_6- modified nitroreductase enzyme prepared in section 1.7, coded by the modified *nfnB* gene located in plasmid pET-28a(+) prepared in Example 1.

2.1 Expression of the enzymes

Using the protocol of Section 1.4, the plasmids prepared
in Example 1 (2 µl) were transformed into competent cells
of the Rossetta strain of *E. coli* (200 µl), which is an
efficient bacterium for the expression of heterologous
5   genes.

The bacteria containing the plasmids were grown overnight
at 37°C in 500 ml of LB plus added kanamycin (50 µg/ml),
until an optical density (O.D.$_{600nm}$) of 0.6 was achieved.
Expression of the cloned genes was induced by addition of
10   isopropyl-beta-D-thiogalactopyranoside (IPTG) (2 ml, 0.1
M: 0.4 mM$^{(final)}$), and grown for a further four hours at
37°C.

The cells were then harvested by centrifuging (8000 rpm
for 10 min) and the resulting pellets were placed on ice
15   and resuspended in imidazole solution (10 mM, 10 ml)
consisting of phosphate buffer (pH 7.4, 6.25 ml, 0.1 M),
and imidazole (2 M, 0.25 ml), made up to 50 ml with
distilled water.   The resulting suspensions were then
sonicated four times for 30s, to break open the cells,
20   whilst avoiding overheating the solution.   The solutions
were then centrifuged (35000 rpm, 5°C, for 45 min).   The
resulting solution contains the nitroreductase (NTR) and
the pellet contains the cell debris.   The solutions were
then run on a sodium dodecyl sulphate-polyacrylamide gel
25   electrophoresis to check that the protein was overproduced
and that its molecular weight was as expected.

2.2 <u>The enzyme purification protocol</u>

The engineered proteins carry a His$_6$ tag at their N-
30   termini, making it easier to purify the protein by eluting
the solution through a nickel-agarose column, where the
histidine residues bind to Ni^{2+} embedded in the resin.
His-tagged target proteins are thus selectively retained

on the column of nickel agarose, and can be eluted
(competitively removed) with imidazole, which competes for
Ni binding sites, displacing the protein.

5   For elution from the column, imidazole solutions (8 ml)
were prepared with increasing concentrations from 50 mM to
1.0 M in sterile filtered distilled water.

The extract of the cells was added to the column dissolved
10 in phosphate buffer containing 10 mM imidazole.   Elution
was carried out according to the maker's instructions
(Amersham Biosciences U.K.) using imidazole concentrations
increasing in stepped amounts.   Each eluate was collected
in 1 ml samples (5 for each concentration) to avoid
15 dilution.   Finally, the column was washed with the
remaining binding buffer (4 ml) and stored below 5°C ready
for reuse.   The second ml of each elute was run on a SDS-
PAGE gel along with the sample flow-through and an induced
unpurified sample.

20

2.3 The removal of imidazole from the protein

The imidazole from the elution stages remains in the
enzyme solution.   It was removed, as stated below, and the
25 nitroreductase (NTR) resuspended in Tris buffer pH 7.2
ready for use on the electrode surface.   A PD-10 desalting
column (Amersham Biosciences U.K.) which is a gravity-
operated polypropylene column containing 8.5 ml of
Sephadex™ G-25 Medium, with a bed height of 5 cm, used for
30 desalting and buffer exchange and was used according to
the manufacturer's instructions.

Example 3 - Characterisation of Enzyme Activity. The activity of the modified nitroreductase enzyme prepared in Example 1 was preferred as follows:

3.1 Nitroreductase assay

A UV assay and associated spectra were carried out on the NTR obtained at the end of Section 2.3 in solution ($\cong$1.0 $\mu M^{(Final)}$, 10 μl), in a cuvette with buffer tris-HCl pH 7.4 (50 mM, 500 μl), NADPH (1 mM, 100 μl), nitroaromatic compound (substrate, various conc.), and flavin mononucleotide (FMN) (1 mM, 5 μl), made up to 1 ml with distilled water at 25°C.

The spectra were collected at a scan rate of 500 nm/min between 220-500 nm resulting in 1 min scans, and the assays were run at 340 nm for 2 min each, using an Uvikon 943 double beam spectrophotometer. The parameters of the spectra and assays are as noted above unless otherwise stated. All spectral measurements were carried out against a blank consisting of the assay solution detailed above, but lacking the nitroreductase enzyme, and all assay measurements were carried out against a blank consisting of the assay solution lacking the substrate, unless otherwise stated.

Example 4 - Preparation of an enzyme biosensor utilising the modified nitroreductase of Example 2.

4.1 Preparation of the gold sheet for UV-vis

Gold was used to prove the concept that the modified enzymes can be immobilised via the thiol groups to gold

substrate and remain active after the immobilisation. Gold sheets were cleaned in a 50:50 mixture of concentrated sulphuric and nitric acid overnight. Desalted and non-desalted Cys-tagged NTR enzymes were

5   each/separately adsorbed onto a gold slide, 3 mm by 5 mm. The gold sheet was left for 24 hours in the nitroreductase solution, and then immersed in buffer (pH 7) to remove any residual proteins.

10   4.2 Electrochemical procedure

Electrochemical measurements were performed using an Autolab PGstat3. The analysis was carried out with a three-electrode cell, using a Saturated Calomel reference electrode (SCE) and a platinum mesh counter electrode.

15   All glassware was cleaned using a 50:50 mixture of concentrated H_2SO_4 : HNO_3 followed by rinsing in purified water, cleaning in a steam bath, and drying in the oven. The working electrode was a gold slide with a self-assembled layer of the appropriate enzyme.

20

The cell contained sodium phosphate buffer pH 7.1 (20 ml, 0.1 M), mixed with the co-factor dicarboxylic ferrocene (50 □M). Additions of the substrate were made by pipetting the desired quantities and concentrations in

25   through the top of the cell.

4.3 Preparation of gold-coated glass slides for electrochemical measurements

30   The gold-coated glass slides obtained from Gold Arrandee™ / Au(111) uses the borosilicate glass (AF45) base material, which is 1.1 +/- 0.1 mm in thickness with the size of the glass slide being 11 x 11 +/- 0.2 mm. The

special glass substrate is well suited for the flame
annealing procedure which is used to obtain Au(111)
terraces. A thin (2.5 +/- 1.5 nm) adhesive layer of
chromium is applied to the glass surface. This layer
5   guarantees optimum adhesion of the gold layer to the
glass. On top of this thin Chromium layer a final gold
layer is applied which is 250 +/- 50 nm thick.

Prior to use, the gold-coated slides were flame-annealed
10   in a Bunsen burner until they attained red heat several
times. After cooling in air for a short period of time,
the slide was quenched in ultrapure water. The slides were
then dipped into an enzyme-containing solution for 24 hrs
at 5°C to assemble the layer of the enzyme. Each slide was
15   then washed in tris-buffer prior to transfer to an
electrochemical cell.

5.1 Assay results
The influence of the nitroreductase on a buffer solution
20   containing 4-nitrobenzoate (625 µM) was assessed using UV-
vis; the nitroreductase (10 µl) was placed in the cuvette
prior to run 2. The results are shown in Figure 4.

The scans show a reduction in the intensity of absorbance
25   at 340 nm on the second scan, followed by reduction of the
absorbance in subsequent scans, down to -0.29 absorbance
units (a.u.). The peak at 300 nm (4-nitrobenzoate)
increased in intensity on the second scan due to
introduction and corresponding absorbance of
30   nitroreductase, then decreased on subsequent scans. The
use of increasing amounts of nitroreductase afforded a
corresponding increase in NADPH conversion, indicating

that the nitroreductase is responsible for the oxidation of NADPH.

As substrates, 4-nitrotoluene, 2,4-dinitrotoluene, 2-
5   ethylhexyl nitrate and nitrobenzene were good substrates whereas 4-nitrobenzoate, 1,2-dinitrobenzene and 2,4-dinitroethylbenzene were excellent substrates (Figure 5).

Both desalted and non-desalted forms of the protein NfnB-
10 cys1 nitroreductase with cysteine tags as prepared hereinabove were adsorbed onto gold slides and scans of the activity towards 2,4-dinitroethylbenzene (DNEB) (620 µmoles) were assessed. The results are shown in Figures 6A and 6B which clearly illustrate the effective catalysis
15 by the desalted enzyme (Fig. 6A).

NADPH is not an efficient co-factor in electrochemical cells because the oxidised form NADP$^+$ produced in the enzyme-catalysed reaction cannot be stoichiometrically
20 reduced to a biologically active form of NADPH electrochemically. For this reason ferrocene dicarboxylic acid (1µm) was used to eliminate this problem, as it exhibits good electrochemical reversibility. The results are shown in Figure 7, using 300µm DNEB with
25 nitroreductase.

The oxidation of the dicarboxylic ferrocene can be seen in the reduced absorbance with time at 280 nm indicating that the ferrocene derivative is being oxidised *via* the
30 enzymatic reaction, hence, can be utilised as the nitroreductase co-factor.

5.2 <u>Specific activity of nitroreductase</u>

The specific activity of nitroreductase was assessed by calculating the rates at different concentrations of substrate in association with the different nitroreductase concentration. The preferred substrate used for both the His-tagged nitroreductase from E. coli (NfnB-his1) and the further modified Cys-tagged enzyme (NfnB-cys1) was 2,4-dinitroethylbenzene   (31   µM).   The   protein concentration was calculated by placing a micro protein-PR™ reagent (1 ml) in 3 cuvettes, a blank, a standard (500 mg/l), and a sample of nitroreductase.   UV measurements were taken at 600 nm in accordance with the procedure. The unpurifed protein was compared against the purified protein.   Four runs were performed for each volume of 5, 10, 15, and 20 µl of protein.

The activity for the enzyme NfnB-his1 before purification was 0.22 □moles/min/mg which rose to 4.65 □moles/min/mg following purification.   Hence, the purification achieved an approximate average of 20-fold increase in activity, with the enzyme making up only 7.6% of the unpurifed solution.   The relevant specific activities are tabulated in Table 1.

Protein	Average total protein (□g/ml)	Average specific activity (□moles/min/mg)
NfnB-his1 **Unpurifed** **Purified**	5.23 0.40	0.22 4.64

NfnB-cys1		
Unpurifed	4.83	0.18
Purified	0.18	2.92

Table 1: The concentration and specific activity for the
unpurifed and purified proteins NfnB-his1 and NfnB-cys1
with 2,4-dinitroethylbenzene.

The protein with the Cys_6 tags (NfnB-cys1) showed that the
insertion of the Cys residues reduced the activity by an
average of ≈37%. After the removal of imidazole from the
protein solutions containing the Cys tags, the proteins
retained approximately 86% of its original activity.

5.3 K_m and V_{max} of the nitroreductase

In order to calculate the K_m and V_{max} values, a plot was
constructed of activity in □□˜min/mg against increasing
concentration of substrates as shown in Figure 8.

The resulting data was used to calculate the K_m and V_{max}
values from Direct Linear method *via* an enzyme kinetics
theory and practice software package (Enzpack). The
resulting data was averaged and obtained with a 68%
confidence level, as shown in Table 2 below.

Proteins	K_m (μmol)	V_{max} (μmol/min/mg)	V_{max}/K_m ratio	Substrate
NfnB-his1	27	27	0.99	2,4-dinitroethylbenzene
NfnB-cys1	33	27	0.84	2,4-dinitroethylbenzene

Table 2 Resulting K_M and V_{max} values for the *E coli*
nitroreductase

The values of K_m and V_{max} are specific to each enzyme
5   however, the ratio V_{max}/K_m can be used to compare the
enzyme efficiency, as shown in Table 2. The efficiency of
the enzyme is ultimately limited by the rate of diffusion
of the substrate to the enzyme and by the chemical events
that occur in the active site of the enzyme.

10
The number of moles of substrate converted to product per
unit of time, known as the turnover number (K_{cat}), also
allows comparisons between the enzymes. The turnover
number can be calculated from the following equation:

15

$$V_{max} = K_{cat}[E_{Tot}]$$

The average K_{cat} of substrate for the two modified NfnB was
6.4×10^2 mol/min/moles of enzyme.

20   5.4 Evaluation of the biosensor; voltammetry results

Cyclic voltammograms were obtained for the unmodified gold
electrode and the gold electrode modified with the
desalted enzyme solution; a seal was made between the
25   working electrode and the electrolyte solution with o-
rings defining a geometric area of 0.6 cm^2. The
modification of the electrodes was achieved by immersing
the gold slide, which is now the working electrode, in the
enzyme solution (0.1 M phosphate butter, pH 7.1) for 24
30   hours, then thoroughly rinsing with sodium phosphate
buffer. The results are shown in Figure 9.

The reduction in the oxidation peak (oxidation of gold surface) at +350 mV is caused by the formation of the layer of enzymes blocking the electrode surface. The presence of the layer is also manifested by the large

5   reduction in the current associated with the hydrogen evolution reaction at -400 mV. In order for the reaction (reduction of nitroaromatics) to proceed, a co-factor needs to be introduced into the solution. A voltammogram of the co-factor, dicarboxylic ferrocene (35μm) in 0.1 M

10   phosphate butter, pH 7.1, was carried out to evaluate an appropriate potential to hold the amperometric sensor at, so that the dicarboxylic ferrocene could be reduced after it has been oxidised during the enzymatic reaction. The results are shown in Figure 10.

15   Figure 11 shows the amperometric response of the biosensor with the NfnB-cys1 enzyme expressed from pMKS2 which was evaluated at a fixed potential of +100 mV in a 0.1 M phosphate buffer (pH 7.1) and the co-factor was dicarboxylic ferrocene (10 mM, 200 □moles). The working

20   electrode was a gold slide modified with NfnB-cys1. and all potential values are quoted against a SCE. Prior to the injection of DNEB (20 μl of 2 □M solution of DNEB resulting in a concentration of 2 nM in the cell), the current was allowed to stabilise for 730 s until a steady

25   state current was reached. After the addition of the DNEB sample, a slight increase in current was observed, thought to be due to convection caused by introducing the substrate.

30   After the initial rise, the current becomes less positive by approximately 10nA. This drop was caused by the reduction of the ferrocenium dicarboxylic acid that had been formed as a result of the oxidation of ferrocene

dicarboxylic   acid   by   the   oxidised   form   of   the
nitroreductase.   The   current   then   starts   to   decay   to   a
value   close   to   the   initial   baseline   value   thus   allowing
successive   readings   to   be   taken.   Further   amperometric

5   measurements   were   carried   out   with   10,   30,   40,   and   50
pmoles   of   DNEB   corresponding   to   0.5   nM,   1.5   nM,   2   nM,   2.5
nM   respectively.   The   larger   the   amount   of   DNEB   that   is
introduced   into   the   system,   the   larger   is   the   drop.   A
linear   relationship   is   found   between   the   magnitude   of   the

10   current   and   the   concentration   of   the   analyte;   thus
providing   a   basis   for   an   amperometric   sensor.   The   results
are   shown   in   Figures   12A   and   12B.   No   response   was   obtained
when   DNEB   was   not   present   in   the   analyte   solution.

15   Figure   12A   shows   amperometric   data   for   the   four   different
concentrations   of   DNEB   at   a   potential   of   +100   mV   in   a   0.1
M   phosphate   buffer   (pH   7.1),   the   working   electrode   was   a
gold   slide   modified   with   NfnB-cys1.   DNEB   samples   were
injected   100   s   after   applying   the   potential;   the   co-factor

20   was   ferrocene   dicarboxylic   (10   mM,   200   µmoles).   Figure   12B
shows   a   plot   of   the   magnitude   of   the   current   drop   taken   70
s   after   the   injection   of   DNEB   from   the   data   in   Figure   12A
against   the   concentration   of   DNEB.   The   plot   is   that   of   a
straight   line   and   shows   a   linear   relationship   between   the

25   magnitude   of   the   current   and   the   concentration   of   the
analyte.

The   lowest   concentration   examined   in   this   case   corresponds
to   a   concentration   of   DNEB   in   the   parts   per   trillion   range

30   (ppt).

Example 6

The above protocols and tests from Sections 1.1 to 5.4 were performed utilising the *Pseudomonas putida* JLR11 *prnA* gene conforming to SEQ ID2 in a pET-28a(+) expression vector comprising the expression sequence shown in SEQ

5 ID4. The results again indicated that excellent sensitivity, in the picomolar range, was exhibited by the resultant biosensor.

Conclusions

10

The results illustrate that the introduction of the cysteine tags at the N-terminus does not reduce the activity in a way that (detrimentally affects/prevents) amperometric measurements, and that the tags were

15 successful in the immobilisation of the enzyme to a gold surface, without the loss of activity. Evidence for the assembly of the nitroreductases on the gold surface was obtained by FTIR, UV-vis spectroscopy, and cyclic voltammetry.

20

The nitroreductase was shown to be active with a range of nitroaromatics and a nitro ester, namely 2-ethylhexyl nitrate, and afforded different rates of reaction for each substrate. The optimum pH (pH 7.1) and temperature (<40

25 °C) for the enzyme were established along with K_M, V_{max}, and turnover numbers (K_{cat}).

The response of the amperometric sensor was in the nanoamp range and detection was unexpectedly down in the parts per

30 trillion region. The drop in current (and the rate of drop) was found to be proportional to the concentration of nitroaromatics in solution, and the system showed evidence of recovery after each sample, allowing successive samples

to be taken. In addition, the enzyme remained active when kept in the fridge for a period of two weeks.